



HD IP



# SONY

**Productnaam** ST-ADST30-IP3MP-Sony 3MP IP PoE vandaalbestendige Dome camera met 30 meter nachtzicht

### Specificaties

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	3MP
Effective Pixels	2065(H)*1553(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time Auto	PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N	Ratio ≥52dB
Scanning System	Progressive
Video Output	Network

### Lens specificaties

Focus lengte	2.8 - 12mm handmatige focus/zoom
Lens type	Varifocale

Pixels	5MP
Infrared	LED 14μ x 24PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power	On CDS Auto Control
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048*1536@30fps
Main Stream 2	1920*1080@30fps
Main Stream 3	/
Sub Stream 1	720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
IE Brower IE8-11	Google Chrome, Firefox, Safari, Mac Safari
Smart Phone iPhone	iPad, Android, Android Pad

### Features

Day/Night Color/ B&W (IR-CUT )	Color / B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
BLC	Support
HDR	Support

<b>WDR</b>	Support
<b>Motion Detection</b>	Support
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Modes</b>	NVR/NAS/CMS/Web
<b>Language</b>	nglish, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands
<b>Audio</b>	Optional
<b>Housing Metal</b>	IP66
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 1100mA
<b>Dimension</b>	φ 131 x 93(H) mm
<b>Weight</b>	800g

---