



Camera specificaties:

Camera model	ST-ProSeries-8MP-Bullet
Camera chipset	1/2.5" Progressive Sony CMOS
Min. verlichting	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Langzame shutter	Ondersteund
Lens	3.3 ~ 12mm (gemotoriseerd) H.FOV: 105 - 37°
F No	F No. W:1.4-T:2.8±5%
Dag & Nacht	IR cut filter with auto switch
WDR	Digitaal
Video compressie	H.265/H.264
Video bitrate	8Kbps ~ 16Mbps
Triple Stream	Ja
Resolutie	Mainstream 8MP (3840×2160),4MP(2592×1520) 3MP(2304×1296),1080P(1920×1080), 720P(1280×720), Substream 1080P(1920×1080),720P(1280×720), VGA(640×480),QVGA(320×240) Mobilestream VGA(640×480),QVGA (320×240)

Beeld instellingen	Roteer mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Ondersteund
ROI	Ondersteund
Privacy Mask	Ondersteund
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Sationary Object Detection, Pedestrian De
Protocollen	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
System compatibiliteit	ONVIF(Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Infrarood leds	40 stuks(SMD)
Infrarood bereik	tot 50 meter
SD opslag	Ja
Alarm schakelaar	Ja
Audio	Ondersteund audio, microfoon is optioneel
Video Output	Ja
Reset knop	Ja
PoE	Interne PoE
Waterbestendig	Ja, IP66 water én stofbestendig
Power Supply	DC 12V/POE
Stroomverbruik	≤ 9W
Gewicht	Ongeveer 720gr
Weerbestendigheid	van -30 tot 55 graden

